



TECHNICAL INFORMATION

Product Description – RCL 1000™ Lubricating Spray

- Designed to resist rust and corrosion
- Specifically designed for thin film, heavy load lubrication applications
- Engineered to reduce friction and drag by forming a high strength boundary film
 - Speeding up drilling and tapping. Cutting edges remain sharper longer
 - Prolonging operating life
- Displaces water, inhibiting oxidation and rust formation
- Designed to withstand corrosive environments
- Compatible with typical seals except EPDM
- Apply with a spray or a brush between rubbing surfaces

Product Description – P2000™ Penetrating Fluid

- Heavy duty performance
- Specifically designed for rapid, deep penetration of rusted or seized parts
- Engineered to cut through the most stubborn corrosion with ease
- Penetrates in wet conditions (displaces moisture)
- Contains no ozone depleting ingredients and is easily mistable
- Designed to reduce rust formation

Typical Properties

Properties	Method	Results – RCL1000™	Results - P2000™
Appearance		Clear, Dark, Amber Liquid	Clear, Light, Amber Liquid
Color	ASTM D1500	2.3	1.6
Viscosity @ 40 °C	ASTM D445	8 cSt	3.8 cSt
Specific Gravity	ASTM D941	0.860	0.825
Density @ 20 °C	ASTM D941	0.860 g/mL	0.825 g/mL
Pour Point	ASTM D97	-36 °C	-67°C
Flash Point (COC)	ASTM D92	130 °C	108°C
Fire Point (COC)	ASTM D92	135 °C	110°C

Available in 17oz. aerosol cans, 500mL bottles, 4L jugs and 20L pails.