## Infinity RCL

The Heavy-Duty lubricator for serious tools boxes. Stays where you spray with polarized film.

**RCL.1000:** All-purpose lubricating fluid can be used on sliding doors, hinges, bicycles, locks, sewing machines, air tools, etc.

## DESIGNED FOR PERFORMANCE

- Specifically designed for thin film, heavy load lubrication applications
- Reduces friction and drag by forming a high strength boundary film
- Speeds up drilling and tapping; cutting edges remain sharper longer
- Prolongs operating life
- Resists rust and corrosion
- Displaces water, inhibiting oxidation (rust)
- Will not tarnish metals
- Designed to withstand corrosive environments
- Compatible with typical seals except EPDM
- Apply with a spray or a brush between rubbing surfaces

PART#	3500-52-12 (52ml x 12)	3500-20-1 (20L Pail)
	3500-425-12 (425ml x 12)	3500-205-1 (205L Drum)
	3500-4-4 (4L x 4)	

TYPICAL PROPERTIES	ASTM METHOD	Needle Oiler
Appearance		Clear, Dark, Amber
Colour	D 1500	2.3
Flash Point	D 92	130
Pour Point	D 97	-36
Fire Point	D 92	135
Viscosity @ 40°C (cSt)	D 445	8 cSt
Specific Gravity	D 445	0.860
Density @ 20°C	D 941	0.860 g/ml

